




BAG STYLES:



QUAD-SEAL
/FLAT-BOTTOM



PILLOW STYLE



BRICK FOLD-DOWN
/TAPE-DOWN



GUSSETED



STANDUP w/
HANDLE



EUROSLOT/
HOLE PUNCH

MAXIMUM SPEED:

Up to **120** cycles
per minute

MAXIMUM BAG SIZE:

400 mm x 600 mm
(15.75" x 23.62")

MINIMUM BAG SIZE:

100 mm x 100 mm
(3.94" x 3.94")

VIKING MASEK VFFS

E250

E400

ES400

M250

M250 BiB

M400

M500

M650

S250

\$400

SACHET SA300-SA500

SIGMA

STICK PACK ST200-ST800

VELOCITY

**ROBUST, SERVO-DRIVEN VERTICAL BAGGER THAT DELIVERS SPEED,
FLEXIBILITY, AND VALUE!**



FEATURES:


- Robust, stainless steel frame
- Enclosed, servo-drive jaw actuation
- Quiet running speeds up to 120 cycles per minute
- Off-the-shelf components
- Minimal maintenance requirements
- No tool changeover
- Self-centering pull belts
- Automatic film tracking
- VFD powered film unwind
- Quick film splice table
- Product stagers
- End-seal cooling air
- Bag deflators
- Photo eye and encoder
- Double guard door
- Jaw obstruction detection
- Runs most film structures
- Siemens control platform
- Storage for 50 product recipes

OPTIONS:


- Quad seal bag assembly
- Flat bottom bag assembly
- Siemens or Allen Bradley control platform
- Impulse sealing for poly film structures
- Integration with variety of fillers, printers, metal detectors, label applicators, and checkweighers
- Washdown construction
- Vacuum pull belts
- Fold-down/tape-down unit
- Hole punch (Euroslot and Round)
- Carry-handle punch
- Load shelf
- Product settler
- Gas flush
- Static eliminator
- Tear notch
- Degassing valve applicator
- In-feed and take-away conveyors
- Remote diagnostics

S400 VIEWS:


FRONT



SIDE



TOP



Standard views, dimensions may vary.

